



LOCATION

La Baña – Northwest Spain

COLOR

True un-fading BLUE-BLACK

FORMAT

Metrics & Imperials.
From 30cm x 20cm (12" x 08") up to 60cm x 35cm (24" x 14")

PRODUCT

Roofing & Cladding slates

CHARACTERISTICS

Real textured appearance. Traditional look.
Pyrite free.
Perfect match for Seca slate.
Large sizes available regularly.

THICKNESS AND WEIGHT

5mm (1/5"); 33 kgs/m²; 655 Lbs/square
6-7mm (1/4"); 46 kgs/m²; 875 Lbs/square
9-10mm(3/8"); 66 kgs/m²; 1275 Lbs/square
12-13mm(1/2"); 80 kgs/m²; 1615 Lbs/square

Slate can be supplied either holed or unholed depending upon the roofing system chosen

Williamsburg is produced from one source of origin and has a long history of exporting high quality slates to the most demanding markets.

The quality control of be natural® staff in the quarry guarantees a perfect selection of your order before the collection.
We control color, thickness, size and labels.

[Watch VIDEO](#)

SLATE FOR DISCONTINUOUS ROOFING AND CLADDING UNE-EN 12326-1 ASTM C-406

Dimension and Dimensional Variation	Complies
Nominal Thickness and Variation	Complies
Mechanical Resistance, Characteristic MoR	Transverse: 40.9 N/mm ² / Longitudinal: 72.7 N/mm ²
Mechanical Resistance, Mean Failure Load	Transverse: 49.9 N/mm ² / Longitudinal: 86.4 N/mm ²
Carbonate Content	0.9 % Complies
Water Absorption	Complies with code W1 0.26%
Thermal Cycling	T1 Complies
Sulphur Dioxide Exposure	S1 Complies
Non-Carbonate Carbon Content	0.4 % Complies
Release of Dangerous Substances	None in conditions of use as roofing or external cladding
External Fire Performance	Deemed to satisfy
Reaction to Fire	Deemed to satisfy CLASS A1



Fireproof



Waterproof



Resistant to
pollution



Long lasting



100% Natural



Environmentally
safe



Hand
selected



Low
maintenance